

TECHNICAL SPECIFICATION

TDS 1A13

Ver.B/02.21

Raltex

Raltex is a water-based emulsion paint for indoor use with high whiteness and very good hiding power. Ideal for surfaces that need frequent recoating. It does not contain ammonia and hazardous substances such as heavy metals, free formaldehyde and aromatic hydrocarbons. Recommended for application in all indoor living spaces. It has low odor and special composition that protects the user and does not burden the environment. It is applied on plaster, concrete, bricks, plasterboards, cement boards, etc. It has excellent workability, does not spatter and dries quickly giving a beautiful mat finish. It has strong adhesion, and reduced content of Volatile Organic Compounds.

APPLICATION

- *Substrate Preparation*
Surfaces must be clean, dry and free of loose materials, dusts, oils, etc. For use on old or loose concrete or plaster surfaces, it is recommended to stabilize the substrate using the **Isacryl Nerou** impregnating primer. For application on new or unpainted surfaces of concrete or plaster, prime with **Drapa Astari Plastikon** or **Isacryl Nerou** impregnating primer. Then apply two layers of **Raltex**. For repainting of smooth surfaces without problematic parts, apply two hands of **Easy Plast** directly.
- *Application*
Brush, roller or pistol, diluted 5-10% with clean water.
- *Spreading rate*
9-11 m²/lt on properly prepared surfaces.
- *Drying time*
Touch dry in 0.5 -1 hour. Recoating after 3-4 hours. The drying time depends on weather conditions (temperature, humidity).
- *Cleaning of tools*
Try to remove as much paint as possible from the tools before cleaning them. Clean tools immediately after use with water and cleaning liquid if needed.
- *Restrictions*
Do not apply the product when the ambient temperature and/or the substrate temperature is lower than 5°C.

PACKAGING

Available in plastic pails of 0.75lt, 3lt and 9lt.

STORAGE

Store in a dry and cool place (5°C to 35°C). Keep container tightly closed.

SAFE USE

Avoid contact with eyes. Consult the product's SDS for more information.

TECHNICAL CHARACTERISTICS

- *Binder:* Acrylic
- *Drying:* Touch dry after 30 min.
- *Repainting:* Minimum after 3hr.
- *Viscosity:* 6000 – 8000 cp (spindle No4, 20 rpm, 25°C).
- *Density:* 1,49-1.51 gr/ml.
- *Thinning:* 5-10% with Clean water.
- *Colors:* Available in white and thousands shades through Drapa Color System.
- *Gloss:* Mat.

VOLATILE ORGANIC COMPOUNDS

EU limit value for this product (cat A/a): 30 gr/lt. This product contains maximum 9 gr/lt VOC.