TECHNICAL SPECIFICATION
TDS 1A14
Ver.C /02.21

EASY HYDRO

Easy Hydro is a water-based emulsion paint for internal use with good hiding power and whiteness. It is suitable for application on surfaces like walls, warehouses, stairways, ceilings and any other surface that needs frequent recoating. It is ideal for recoating of old surfaces already coated with products based on cellulosic binder or low-quality, water-based emulsion paints. It can be applied on various substrates such as plaster, plasterboards etc. It has very good workability good leveling and dries fast giving a wonderful mat finish. With very low Volatile Organic Compounds content.

APPLICATION

- *Substrate Preparation*
  Surfaces must be clean, dry and free of loose materials, dusts, oils, etc. For use on surfaces painted with cellulosic based products, old or loose concrete and plaster surfaces, is recommended to stabilize the substrate using the **Isacryl Nerou** impregnating primer. For application on new or unpainted surfaces of concrete or plaster, prime with **Drapa Astari Plastikon** or **Isacryl Nerou** impregnating primer. Then apply two layers of **Easy Hydro**. For repainting of smooth surfaces without problematic parts, apply two hands of **Easy Hydro** directly.
- *Application*
  Brush, roller or pistol, diluted 5-10% with clean water.
- *Spreading rate*
  9-10 m^2/lt on properly prepared surfaces.
- *Drying time*
  Touch dry in 0.5 -1 hour. Recoating after 3-4 hours. The drying time depends on weather conditions (temperature, humidity).
- *Cleaning of tools*
  Try to remove as much paint as possible from the tools before cleaning them. Clean tools immediately after use with water and cleaning liquid if needed.
- *Restrictions*
  Do not apply the product when the ambient temperature and/or the substrate temperature is lower than 5^{o}C.

DRAPA CHEMIE - DRAKOPOYLOS S.A.
Megaridos Ave & Chiou Str, Mavri Yiora Area,
19300, Aspropyrgos, Attiki, Greece
tel: +302105570191, fax: +302105593945
Email: drapa1@otenet.gr, Url: www.drapa.gr
EN ISO 9001:2015, Cert. Nr. 123045
EN ISO 14001:2015, Cert. Nr. GR/002/2015-3

PACKAGING

Available in plastic pails of 3lt and 9lt.

STORAGE

Store in a dry and cool place (5°C to 35°C). Keep container tightly closed.

SAFE USE

Avoid contact with eyes. Consult the product's SDS for more information.

TECHNICAL CHARACTERISTICS

- *Binder:* Acrylate.
- *Drying:* Touch dry after 30 min.
- *Repainting: Minimum after 3*hr.
- Viscosity: 6000 – 8000 cp (spindle No4, 20 rpm, 25°C).
- *Density:* 1,48-1,50 gr/ml.
- *Thinning: 5-10% with* Clean water.
- *Colors:* Available in white.
- *Gloss:* Mat.

VOLATILE ORGANIC COMPOUNDS

EU limit value for this product (cat A/a): 30 gr/lt. This product contains maximum 5 gr/lt VOC.

DRAPA CHEMIE - DRAKOPOYLOS S.A.
Megaridos Ave & Chiou Str, Mavri Yiora Area,
19300, Aspropyrgos, Attiki, Greece
tel: +302105570191, fax: +302105593945
Email: drapa1@otenet.gr, Url: www.drapa.gr
EN ISO 9001:2015, Cert. Nr. 123045
EN ISO 14001:2015, Cert. Nr. GR/002/2015-3