

TECHNICAL SPECIFICATION

TDS 1A17

Ver.B/02.21

EASY ELASTIC

Easy Elastic is a top quality 100% acrylic, sealant and waterproofing, elastomeric paint for outdoor use. It has excellent resistance to alkali and UV radiation, very high whiteness and supreme hiding power. It does not contain ammonia and hazardous substances such as heavy metals, free formaldehyde or aromatic hydrocarbons. It has low odor and a specially designed composition that protects the user and does not burden the environment. Recommended for application on surfaces such as concrete, plaster, masonry, cement boards, etc. It remains elastic even in very low temperatures and it can cover capillaries and small cracks. It has excellent workability and dries quickly. Its adhesion is supreme, giving the surface long-term protection from adverse weather conditions.

APPLICATION

- **Substrate Preparation**
Surfaces must be clean, dry and free of loose materials, dusts, oils, etc. For use on old or loose concrete or plaster surfaces, it is recommended to stabilize the substrate using the **Isacryl** impregnating primer. For application on new or unpainted surfaces of concrete or plaster, prime with **Isacryl** or **Isacryl Nerou** impregnating primers. Then apply two layers of **Easy Elastic**. For repainting of smooth surfaces without problematic parts, apply two hands of **Easy Elastic** directly.
- **Application**
Brush, roller or pistol, diluted 5-10% with clean water.
- **Spreading rate**
10-12 m²/lt on properly prepared surfaces.
- **Drying time**
Touch dry in 0.5 -1 hour. Recoating after 3-4 hours. Drying times depend on weather conditions (temperature, humidity) and vary accordingly.
Cleaning of tools
Try to remove as much paint as possible from the tools before cleaning them. Clean tools immediately after use with water and cleaning liquid if needed.
- **Restrictions**
Do not apply the product when the ambient temperature and/or the substrate temperature is lower than 5°C. Special care should be taken so that in the next 2-3 days after application there is no forecast of rain.



PACKAGING

Available in plastic pails of 0.75lt, 3lt and 10lt.

STORAGE

Store in a dry and cool place (5°C to 35°C). Keep container tightly closed.

SAFE USE

Avoid contact with eyes. Consult the product's SDS for more information.

TECHNICAL CHARACTERISTICS

- *Binder:* 100% Acrylic, elastomeric
- *Repainting:* Minimum after 3hr.
- *Viscosity:* 7000 – 9000 cp (spindle No4, 20 rpm, 25°C).
- *Density:* 1,48-1.50 gr/ml.
- *Thinning:* 5-10% with Clean water.
- *Colors:* Available in white and thousands more through the **Drapa Color System**.
- *Gloss:* Mat.

VOLATILE ORGANIC COMPOUNDS

EU limit value for this product (cat A/c): 40 gr/lt. This product contains maximum 25 gr/lt VOC.

DRAPA
chemie

DRAPA CHEMIE - DRAKOPOYLOS S.A.
Megaridos Ave & Chiou Str, Mavri Yiora Area,
19300, Aspropyrgos, Attiki, Greece
tel: +302105570191, fax: +302105593945
Email: drapa1@otenet.gr, Url: www.drapa.gr
EN ISO 9001:2015, Cert. Nr. 123045
EN ISO 14001:2015, Cert. Nr. GR/002/2015-3

