

TECHNICAL SPECIFICATION

TDS 1A06

Ver .C /02.21

EASY PROOF

Easy Proof is a water based acrylic insulating coating. It is an excellent solution for economic and reliable waterproofing. It can be applied on surfaces such as concrete or tiled roofs, roof edges, drains etc. It has very good adhesion, high elasticity and resistance to changing weather conditions. It remains virtually unaffected by the salts and the alkaline environment of plasters and concrete, and is resistant to weathering and UV radiation. It is easy to apply and its elasticity makes it to follow the contraction-expansion of the coated surfaces.

APPLICATION

- **Substrate Preparation**
Surfaces must be clean, dry and free from loose pieces, dirt, grease etc. On new or uncoated surfaces apply a first coat as Primer thinned up to 20% with water. For use on old or loose surfaces stabilization of the substrate using the primer **ISACRYL** is recommended. Apply **Easy Proof** in two layers diluted up to 10% with water. The second layer is applied crosswise 24 hours later and after the first one has dried. A total consumption of at least 0.8lt per square meter is recommended. The application must be done in non-rainy conditions, at temperature greater than 5 degrees and less than 35 ° C. Especially in summer the application should be done early in the morning or late afternoon.
- **Application**
Paintbrush, roller or airless spray diluted 5-10% with clean water.
- **Consumption**
- 1,2 m²/lt (priming plus two coats, depending on the absorbability of the surface).
- **Drying time**
Touch dry after 2-3 hours. Recoat after 24 hours. Drying times depends strongly on weather conditions like humidity and temperature.
- **Cleaning of tools**
Try to remove as much paint as possible from the tools before cleaning them. Clean tools immediately after use with water and cleaning liquid if needed.
- **Restrictions**
Do not apply the product when the ambient temperature and/or the substrate temperature is lower than 5°C. Special care should be taken so that in the next 2-3 days after application there is no forecast of rain.

PACKAGING

Available in plastic pails of 3lt and 10lt.

STORAGE

Store in a dry and cool place (5°C to 35°C). Keep container tightly closed.

SAFE USE

Avoid contact with eyes. Consult the product's SDS for more information.

TECHNICAL CHARACTERISTICS

- *Binder:* 100% Acrylic, elastomeric
- *Solids:* 63±0,5%
- *Drying Times:*
Surface: 1hr
In depth: 3hr
Full curing: 72hr
- *Repainting:* Minimum after 16hrs.
- *Viscosity:* 18000– 20000 cp (spindle No4, 20 rpm, 25°C).
- *Density:* 1,37-1.39 gr/ml.
- *Thinning:* 5-10% with Clean water.
- *Colors:* Available in white.
- *Finish:* Satin.

VOLATILE ORGANIC COMPOUNDS

EU limit value for this product (cat A/c): 40 gr/lt. This product contains maximum 20 gr/lt VOC.