TECHNICAL SPECIFICATION
TDS 1B05
Ver.B/03.21

BETOPRIM BLOCK

Betoprim Block is a white, covering, water-based, 100% acrylic, stain blocking undercoat. It is ideal for all interior and exterior masonry surfaces. It isolates and covers stains of smoke, nicotine, yellowness, water soluble pen, coffee, juice, old dampness, etc. It stops the transfer of water soluble dirt to the surface of the top coat while it's very high hiding power ensures a very efficient and cost saving painting, as less layers of top coat paint are needed. It does not contain ammonia and dangerous substances such as heavy metals, free formaldehyde and aromatic hydrocarbons. Recommended for application in all indoor living spaces. It has low odor and a specially designed composition that protects the user and does not burden the environment. It has very good workability end excellent spreading and levelling. It can be over coated with all kind of waterborne coatings (latex, acrylic, etc). It dries fast giving to the substrate an excellent mat finish ideal for a flawless application of the top coat.

APPLICATION

- *Substrate Preparation*
  Surfaces should be clean, dry and free from unsound materials, dust, oils, etc. Apply one coat of **Betoprim** thinned up to 10%. For application on soiled or highly absorbent surfaces it is recommended to apply a second –more concentrated– coat of **Betoprim**. In such cases, apply the final coat the next day.
- *Application*
  Brush, roller or pistol, diluted 5-10% with clean water.
- *Spreading rate*
  11-13 m^2/lt on properly prepared surfaces and depending on the dilution and the absorptivity of the substrate.
- *Drying time*
  Touch dry in 0.5 -1 hour. Recoating after 4-5 hours. The drying time depends strongly on weather conditions (temperature, humidity).
- *Cleaning of tools*

DRAPA chemie
DRAPA CHEMIE - DRAKOPOYLOS S.A.
Megaridos Ave & Chiou Str, Mavri Yiora Area,
19300, Aspropyrgos, Attiki, Greece
tel: +302105570191, fax: +302105593945
Email: drapa1@otenet.gr, Url: www.drapa.gr
EN ISO 9001:2015, Cert. Nr. 123045
EN ISO 14001:2015, Cert. Nr. GR/002/2015-3

Try to remove as much paint as possible from the tools before cleaning them. Clean tools immediately after use with water and cleaning liquid if needed.

- *Restrictions*
  Do not apply the product when the ambient temperature and/or the substrate temperature is lower than 5°C.

PACKAGING

Available in plastic pails of 0.75lt, 3lt and 10lt.

STORAGE

Store in a dry and cool place (5°C to 35°C). Keep container tightly closed.

SAFE USE

Avoid contact with eyes. Consult the product's SDS for more information.

TECHNICAL CHARACTERISTICS

- *Binder:* Acrylic
- *Drying:* Touch dry after 30 min.
- *Repainting: Minimum after 4* hrs.
- Viscosity: 8000 – 10000 cp (spindle No4, 20 rpm, 25°C).
- *Density:* 1,46-1.48 gr/ml.
- *Thinning: 5-10% with* Clean water.
- *Colors:* Available in white.
- *Gloss:* Mat/slightly satine.

VOLATILE ORGANIC COMPOUNDS

EU limit value for this product (cat A/g): 30 gr/lt. This product contains maximum 25 gr/lt VOC.

DRAPA CHEMIE - DRAKOPOYLOS S.A.
Megaridos Ave & Chiou Str, Mavri Yiora Area,
19300, Aspropyrgos, Attiki, Greece
tel: +302105570191, fax: +302105593945
Email: drapa1@otenet.gr, Url: www.drapa.gr
EN ISO 9001:2015, Cert. Nr. 123045
EN ISO 14001:2015, Cert. Nr. GR/002/2015-3